APPROX. PRODUCT MASS

INSTALLED MASS:	3200	LBS
SHIPPING MASS:	3410	LBS

REVISIONS				
REV	EC#	DESCRIPTION	DRAWN	DATE
Α	489	INITIAL RELEASE	A. FITZPATRICK	3/26/2013
В	1388	NEW REVISION OF AIR INTAKE SHROUDS ADDED SHROUDS TO EXHAUST	A. MARINELLA	4/14/2015


NOTES:


- 1. SEE SOLECTRIA RENEWABLES SGI 500XT INSTALLATION AND OPERATION MANUAL FOR FURTHER INSTALLATION REQUIREMENTS. 2.
 - CUSTOMER INTERFACE DRAWING SHEETS INCLUDE:
 - FRONT ISOMETRIC 1.
 - 2. 3. FRONT
 - REAR
 - 4. RIGHT
 - 5. LEFT
 - 6. 7. TOP
 - BOTTOM
 - DC CONDUCTOR CONNECTIONS 8.
 - 9. DC GROUND CONNECTIONS10. AC CONDUCTOR CONNECTIONS

 - 11. AC CONDUCTOR CONNECTIONS WITH OPTIONAL AC BREAKER OR DISCONNECT
 - 12. AC GROUND CONNECTIONS
 - 13. SIGNAL WIRE ROUTING LOCATIONS
 - 14. AS SHIPPED ISOMETRIC
 - 15. RECOMMENDED RIGGING AND LIFTING METHODS





CUSTOMER INTERFACE DRAWING PLEASE NOTE: ALL INFORMATION CONTAINED WITHIN THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE SCALE: 1:16 SHEET 1 OF 15














NOTES:

1.



ISO 04-04-26 REV. A-DRAFT1


SCALE: 1:12


LEFT


ROD


VIEW:


DOCUMENT

















SHEET 11 OF 15

SCALE: 1:6







SECTION VIEW : RIGHT INTERIOR WALL




NOTES: 1. THE INVERTER IS SHIPPED ON AN OVERSIZED SHIPPING PALLET. IT IS RECOMMENDED TO KEEP THE INVERTER SECURED TO THE PALLET AND MOVED AS CLOSE AS POSSIBLE TO THE FINAL LOCATION PRIOR TO REMOVING THE PALLET.






NOTES:

- RECOMMENDED SINGLE POINT LIFTING METHOD SHOWN. SEE SOLECTRIA RENEWABLES SGI 500XT INSTALLATION AND OPERATION MANUAL FOR PREFERED LIFTING METHODS. Ι.
- REFERENCE SOLECTRIA RENEWABLES SGI 500XT INSTALLATION AND OPERATION MANUAL FOR ADDITIONAL LIFTING AND 2. INSTALLATION REQUIREMENTS.





ISO 04-04-26 REV. A-DRAFT1



Π·