

YASKAWA

SOLECTRIA XGI 1000

Premium 3-Ph Transformerless Commercial String Inverters

Features

- Made in the USA with global components
- Buy American Act (BAA) compliant
- 60kW and 65kW
- Built to last
- Lowest cost of labor/installation
- Access to all inverters on-site via WiFi from one location
- Lowest cost of O&M
- Remote diagnostics
- Remote software & firmware upgrades
- 5-90° installation angles
- 4 MPPTs
- Advanced grid-support functions
- Integrated AFCI

Options

- Plug & play MC4 or H4 connectors
- Web-based monitoring
- Revenue grade metering



Yaskawa Solectria Solar's XGI 1000 commercial string inverters are designed for high reliability and built with the highest quality components. Components were selected, tested and proven to last beyond their warranty. The XGI 1000 inverters provide advanced grid-support functionality and meet the latest IEEE 1547 and UL 1741 standards for safety. Offering a wide mounting-angle range (5 – 90° from horizontal), the XGI inverters can be installed to meet NEC array-level rapid shutdown requirements. Designed and engineered in Lawrence, MA, the XGI inverters are assembled and tested at Yaskawa America's facilities in Buffalo Grove, IL.

The all new XGI 1000 inverters are Made in the USA with global components and are compliant with the Buy American Act.

MADE IN THE USA



With U.S. and Global Components

SOLECTRIA SOLAR

SOLECTRIA XGI 1000

Specifications

	XGI 1000-60/60	XGI 1000-60/65	XGI 1000-65/65
DC Input			
Absolute Maximum Input Voltage	1000 VDC	1000 VDC	1000 VDC
Maximum Power Input Voltage Range (MPPT)	580-850 VDC	600-850 VDC	600-850 VDC
Operating Voltage Range (MPPT)	350-950 VDC	350-950 VDC	350-950 VDC
Maximum Operating Input Current	105.6 A (26.4 A per zone)	105.6 A (26.4 A per zone)	110.6 A (27.65 A per zone)
Maximum Operating PV Power (per MPPT)	15.3 kW	15.3 kW	16.6 kW
Maximum Rated PV Input (per MPPT)	22.5 kW	22.5 kW	24.4 kW
Number of MPP Trackers	4 / 1 (default)	4 / 1 (default)	4 / 1 (default)
Number of PV Source Circuits (Fused Inputs)	4 per MPPT; 16 total	4 per MPPT; 16 total	4 per MPPT; 16 total
Maximum PV Current (Isc x 1.25) per Zone / Single Zone	50 A / 180 A	50 A / 180 A	50 A / 180 A
Maximum Recommended DC to AC Ratio	1.5	1.5	1.5
AC Output			
Nominal Output Voltage	480 VAC, 3-Ph	480 VAC, 3-Ph	480 VAC, 3-Ph
AC Voltage Range	-12 / +10%	-12 / +10%	-12 / +10%
Continuous Real Output Power	60 kW	60 kW	65 kW
Continuous Apparent Output Power	60 kVA	65 kVA	65 kVA
Maximum Output Current	72.2 A	78.2 A	78.2 A
Nominal Output Frequency	60 Hz	60 Hz	60 Hz
Power Factor (Unity default)	+/- 0.85 Adjustable	+/- 0.85 Adjustable	+/- 0.85 Adjustable
Total Harmonic Distortions (THD) @ Rated Power	<3%	<3%	<3%
Grid Connection Type	3-Ph + N/GND	3-Ph + N/GND	3-Ph + N/GND
Fault Current Contribution (1 cycle RMS)	93.9 A	101.7 A	101.7 A
Recommended AC Overcurrent Device Rating	100 A (AC Maximum Output Current x 1.25)		
Efficiency			
Peak Efficiency	98.2%	98.2%	98.2%
CEC Average Efficiency	98.0%	98.0%	98.0%
Tare Loss	<1 W	<1 W	<1 W
Temperature			
Ambient Temperature Range	-40°F to 140°F (-40°C to 60°C)		
De-Rating Temperature	122°F (50°C)	113°F (45°C)	
Storage Temperature Range	-40°F to 167°F (-40°C to 75°C)		
Relative Humidity (non-condensing)	0-95%		
Operating Altitude	9,842.5 ft (3,000 m)		
Communications			
Advanced Graphical User Interface	WiFi		
Communication Interface	RJ-45 Ethernet		
Third-Party Monitoring Protocol	Sunspec Modbus TCP/IP		
Web-Based Monitoring	Optional		
Revenue Grade Metering	Optional		
Firmware Updates	Remote/Local		
Testing & Certifications			
Safety Listings & Certifications	UL 1741 / IEEE 1547, UL 1699B, UL 1998		
Advanced Grid Support Functionality	Rule 21, UL 1741SA (pending)		
Testing Agency	Intertek		
FCC Compliance	FCC Part 15, Class A		
Warranty			
Standard Limited Warranty	10 Years		
Enclosure			
Acoustic Noise Rating	55 dBA @ 3 m		
DC Disconnect	Integrated, 2 Pole		
Mounting Angle	5-90° Measured from horizontal		
Dimensions (H x W x D)	45.8 in. x 28.3 in. x 11.6 in. (1163 x 719 x 295 mm)		
Weight	Inverter: 123 lbs (55.8 kg); Wiring Box: 53 lbs (24.1 kg)		
Enclosure Rating and Finish	Type 4, Polyester Powder-Coated Aluminum		

Specifications subject to change.

SOLECTRIA SOLAR

Yaskawa Solectria Solar
360 Merrimack Street
Lawrence, MA 01843
solectria.com

1-978-683-9700
inverters@solectria.com

DOCR-070604-L | April 2019
© 2019 Yaskawa Solectria Solar

YASKAWA